

R920-MX

Connected Crosswalk Beacon or Sign with Overhead Lighting Fixture

Boost safety at unsignalized crossings with proven technology, actionable alerts, and street-level data.

- ✓ Every system ships with **3 years of free remote connectivity**
- ✓ Actionable email and text alerts
- ✓ Remote system access via MX Cloud™
- ✓ Quick setup and local access with MX Field App™ (iOS®/Android™)
- ✓ 'Smart module' design for simple installation and richer data
- ✓ Area/roadway-specific optic provides uniform illumination consistent with IES recommendations
- ✓ Solar Power Report (SPR) available for every location

Free out-of-the-box connectivity

R920-MX systems have connectivity embedded into their design, making installation easy. From the moment a system receives power, it connects both locally to the MX Field App and remotely to MX Cloud, providing easy remote access to system status, settings and data. RRFB systems come with default settings that meet MUTCD Standards, including wig-wag plus simultaneous (WW+S) flash pattern.

Timely and actionable alerts

Cities can enable email and text alerts so they can know the minute there's an issue, be it a knockdown, dead battery or something else. Detailed location and module information reduce downtime and boost site visit efficiency while providing optimal citizen safety.

Comprehensive asset visibility and data collection

All MX systems come with MX Cloud, a web-based application that lets users remotely access system locations, alerts, settings and data like daily activation counts. The GPS map not only gives cities better visibility, but enables streamlined, proactive asset management and future planning.

Long-lasting, reliable operation

Every MX module is built to last with durable, weatherproof aluminum construction and vandal-resistant wireless antennas. Solar-powered models are solar-sized to project locations, backed by a Solar Power Report (SPR) to prove year-round sustainability.



Meets MUTCD Standards



Buy America/
BABA compliant



3-year limited
warranty



carmanah®
MX Series



MX Series Connective Capabilities



What's a Solar Power Report™ (SPR)?

No matter where you install your solar-powered system, your product should be carefully sized for its location to ensure it will be operational for the long-term.

Over the last 20+ years, our engineers have developed a field-proven software simulation that helps us replicate the real-life conditions of your project location—and determine the best solar-powered solution for your project.

Learn more about our process at carmanah.com/spr.

R920-MX

Connected Crosswalk Beacon or Sign with Overhead Lighting Fixture




carmanah® MX Series

carmanah.com | traffic@carmanah.com | 1-844-412-8395

MX FLASHER MODULES



MX RRFB Module



MX Beacon Module



MX LED Sign Module

MX RRFB Module	Meets 11th Ed. MUTCD (Chapter 4L) and MUTCD (Canada) Standards
	Purpose-built optics exceed SAE J595 class 1 intensity by 2.5-3x when used as recommended; meet SAE J578 chromaticity
	3" (76 mm) x 7" (178 mm) clear, UV-rated polycarbonate lens with yellow LEDs and side-emitting pedestrian confirmation LEDs
	Stainless steel mounting brackets make back-to-back installation simple and enable in-field aiming for maximum effectiveness
	Yellow or black powder-coated light bar covers
	Light bar configuration: uni-directional or bi-directional
MX Beacon Module	RRFB backplate and mast arm mount available
	In-field aiming: rotate the light bar towards the incoming vehicle lane, independent of the wire hole location
MX LED Sign Module	Configurable to MUTCD 11th Ed. (Chapter 4S) Standard
	12" (305 mm) or 8" (203 mm) diameter LED modules, yellow
	Yellow or black heads in UV-resistant polycarbonate or aluminum
Options	Side of pole arm and top of pole mount kits available
	Meets MUTCD 11th Ed. (Chapter 2A.12) Standards
	3M High Intensity Prismatic or Diamond Grade retroreflective sheeting and components
	UV-resistant polycarbonate channels and waterproof housings protect wiring; include fully integrated junction box
Options	Standard 30" and 36" W11-2 and S1-1 sign sizes (others available)
	Standard yellow and fluorescent yellow-green sign colors available
	Standard banding, through bolt and U-bolt mount kits available
Options	Audible Information Device (AID) push button
	Passive pedestrian detection

OVERHEAD LED FIXTURE SPECIFICATIONS

LED Fixture	Cree® LED Street/Area Luminaire
Performance	NanoOptic® Precision Delivery Grid™ optic delivers site-specific customization of light quality with increased lumens, improved uniformity ratios, and controlled high-angle brightness
	Up to 11,875 initial delivered lumens
	Up to 125 lumens per watt (LPW)
Optics	Minimum 70 CRI
	4000K color temperature (CCT)
Operation	Type IV Medium (4ME)
Mounting	Fixture operates in conjunction with crosswalk beacons
	Mounts on 1.25" (32 mm) IP, 1.66" (42 mm) O.D. or 2" (51 mm) IP, 2.375" (60 mm) O.D. horizontal tenons (minimum 8" [203mm] in length)
Dimensions & Weight	Direct arm available for fixture mounting
	23.7 x 9.3 x 5.8" (601 x 237 x 148 mm)
	14.2 lb (6.4 kg)





INCLUDED WITH EVERY SYSTEM

MX Subscriptions	3 years out-of-the-box remote connectivity with MX Lite
	See all MX subscriptions
MX Cloud	MX Cloud for remote health status monitoring, email/SMS alerts, scheduling, asset management, programming and more
MX Field App	Bluetooth® mobile app for on-site setup, local access to default settings, system health status and more
Warranty	3-year limited warranty on MX system
	1-year limited warranty on batteries
Support	Carmanah's North American product support technologists available for solution building, solar sizing and troubleshooting
	24/7 access to Carmanah's online Product Support Center
Customize	Build an R920-MX online

MX POWER MODULES

Solar	12 VDC operation, solar sized to specific geographic location
	Includes 12-month Solar Power Report to ensure sustainability
	System designed for 5+ year battery life
AC (only MX 300/400)	Replaceable, recyclable, sealed, maintenance-free AGM batteries offer the widest temperature range and longest life
	100-240 VAC in standard configurations
Construction	Weatherproof, gasketed enclosure with vents for ambient air transfer (NEMA 3R)
	Lockable door
	Cabinet systems include Type II lock option (standard for MX 400)
	Corrosion-resistant aluminum with stainless steel hardware
	Raw aluminum finish or black powder-coated



	MX 100	MX 200	MX 300	MX 400
Type	Integrated solar + battery	Integrated solar + battery	Separate solar + cabinet	Separate solar + cabinet
Housing Dimensions & Weight (w/o batteries)	12.6 x 13.6 x 5.3" 320 x 345 x 135 mm 5 lb (2.3 kg)	30 W version: 18.3 x 15.7 x 5.8" 465 x 399 x 147 mm 11 lb (5.0 kg) 50 W version: 18.3 x 26.3 x 5.8" 465 x 668 x 147 mm 14 lb (6.4 kg)	16.7 x 11.3 x 7.0" 424 x 287 x 178 mm 10 lb (4.5 kg) AC version weight: 12 lb (5.4 kg)	21.9 x 16.1 x 8.3" 556 x 409 x 211 mm 19 lb (8.6 kg) AC version weight: 21 lb (9.5 kg)
Mount Kits				
	Top of Pole Mount	Side of Pole Mount	Top of Pole Mount	Side of Pole Mount
	Universal solar mounts: <ul style="list-style-type: none">• 2-2.5" perforated square posts• 2.38-2.88" OD round poles• 3.5-4.5" OD round poles• Side of pole		Cabinet mounts: <ul style="list-style-type: none">• Standard banding• Through bolts• U-bolts (MX 400 only) Universal solar mounts: <ul style="list-style-type: none">• 3.5-4.5" OD round poles• Side of pole	
Batteries	1-2x 7 Ah	1-2x 18 Ah	1x 18, 35 or 55 Ah	1x 35, 55 or 100 Ah
Solar	15 W	30 or 50 W	50, 80 or 170 W	50, 80 or 170 W
Solar Dimensions & Weights	See housing dimensions above	See housing dimensions above	50 W: 26.3 x 21.2" (668 x 538 mm) 10 lb (4.5 kg)	59.1 x 26.3" (1500 x 668 mm) 25 lb (11.3 kg)
			80 W: 30.7 x 26.5" (780 x 672 mm) 13 lb (5.9 kg)	
			170 W: 59.1 x 26.3" (1500 x 668 mm) 25 lb (11.3 kg)	

WIRELESS COMMUNICATION AND DATA COLLECTION

Local	MX Field App (Bluetooth®)
System-To-System	Linked MX systems flash in sync up to 1,000 ft (305 m) away
Remote	MX Cloud (cellular)
Location & Time	GPS

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Carmanah Technologies is under license. Other trademarks and trade names are those of their respective owners. Android is a trademark of Google LLC.

Specifications subject to local environmental conditions, and may be subject to change.

All Carmanah products are manufactured in facilities that are certified to ISO quality standards.

"Carmanah" and Carmanah logo are trademarks of Carmanah Technologies Corp.

© 2024, Carmanah Technologies Corp. Document: Carmanah_DATA_R920-MX-OHL_RevG